


MMBT2222 / MMBT2222A

NPN Silicon Epitaxial Planar Transistor

for switching and amplifier applications



1. Base 2. Emitter 3. Collector
SOT-23 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage MMBT2222 MMBT2222A	V_{CBO}	60 75	V
Collector Emitter Voltage MMBT2222 MMBT2222A	V_{CEO}	30 40	V
Emitter Base Voltage MMBT2222 MMBT2222A	V_{EBO}	5 6	V
Collector Current	I_C	600	mA
Power Dissipation	P_{tot}	350	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

MMBT2222 / MMBT2222A

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
DC Current Gain at $V_{CE} = 10 \text{ V}$, $I_C = 0.1 \text{ mA}$ at $V_{CE} = 10 \text{ V}$, $I_C = 1 \text{ mA}$ at $V_{CE} = 10 \text{ V}$, $I_C = 10 \text{ mA}$ at $V_{CE} = 1 \text{ V}$, $I_C = 150 \text{ mA}$ at $V_{CE} = 10 \text{ V}$, $I_C = 150 \text{ mA}$ at $V_{CE} = 10 \text{ V}$, $I_C = 500 \text{ mA}$	h_{FE}	35	-	-
	h_{FE}	50	-	-
	h_{FE}	75	-	-
	h_{FE}	50	-	-
	h_{FE}	100	300	-
	h_{FE}	30	-	-
	h_{FE}	40	-	-
Collector Base Cutoff Current at $V_{CB} = 50 \text{ V}$ at $V_{CB} = 60 \text{ V}$	I_{CBO}	-	100	nA
		-	100	nA
Emitter Base Cutoff Current at $V_{EB} = 3 \text{ V}$	I_{EBO}	-	100	nA
Collector Base Breakdown Voltage at $I_C = 10 \mu\text{A}$	$V_{(BR)CBO}$	60	-	V
		75	-	V
Collector Emitter Breakdown Voltage at $I_C = 10 \text{ mA}$	$V_{(BR)CEO}$	30	-	V
		40	-	V
Emitter Base Breakdown Voltage at $I_E = 10 \mu\text{A}$	$V_{(BR)EBO}$	5	-	V
		6	-	V
Collector Emitter Saturation Voltage at $I_C = 150 \text{ mA}$, $I_B = 15 \text{ mA}$ at $I_C = 500 \text{ mA}$, $I_B = 50 \text{ mA}$	$V_{CE(sat)}$	-	0.4	V
		-	0.3	V
		-	1.6	V
		-	1	V
Base Emitter Saturation Voltage at $I_C = 150 \text{ mA}$, $I_B = 15 \text{ mA}$ at $I_C = 500 \text{ mA}$, $I_B = 50 \text{ mA}$	$V_{BE(sat)}$	-	1.3	V
		0.6	1.2	V
		-	2.6	V
		-	2	V
Transition Frequency at $V_{CE} = 20 \text{ V}$, $-I_E = 20 \text{ mA}$, $f = 100 \text{ MHz}$	f_T	300	-	MHz
Collector Output Capacitance at $V_{CB} = 10 \text{ V}$, $f = 100 \text{ KHz}$	C_{ob}	-	8	pF
Delay Time at $V_{CC} = 30 \text{ V}$, $V_{BE(OFF)} = 0.5 \text{ V}$, $I_C = 150 \text{ mA}$, $I_{B1} = 15 \text{ mA}$	t_d	-	10	ns
Rise Time at $V_{CC} = 30 \text{ V}$, $V_{BE(OFF)} = 0.5 \text{ V}$, $I_C = 150 \text{ mA}$, $I_{B1} = 15 \text{ mA}$	t_r	-	25	ns
Storage Time at $V_{CC} = 30 \text{ V}$, $I_C = 150 \text{ mA}$, $I_{B1} = -I_{B2} = 15 \text{ mA}$	t_{stg}	-	225	ns
Fall Time at $V_{CC} = 30 \text{ V}$, $I_C = 150 \text{ mA}$, $I_{B1} = -I_{B2} = 15 \text{ mA}$	t_f	-	60	ns

MMBT2222 / MMBT2222A




Fig.1 Grounded emitter output characteristics




Fig.3 DC current gain vs. collector current(I)




Fig.2 Collector-emitter saturation voltage vs. collector current




Fig.4 DC current gain vs. collector current(II)




Fig.5 AC current gain vs. collector current




Fig.6 Base-emitter saturation voltage vs. collector current

Fig.7 P_c - T_a

