


MMTSB1198

PNP Silicon Epitaxial Planar Transistor

Low frequency transistor

The transistor is subdivided into two groups Q and R, according to its DC current gain.



1.BASE 2.EMITTER 3.COLLECTOR

SOT-23 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage	$-V_{CBO}$	80	V
Collector Emitter Voltage	$-V_{CEO}$	80	V
Emitter Base Voltage	$-V_{EBO}$	5	V
Collector Current	$-I_C$	0.5	A
Collector Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{Stg}	-55 to +150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $-V_{CE} = 3 \text{ V}$, $-I_C = 100 \text{ mA}$	Q	h_{FE}	120	-	270
	R	h_{FE}	180	-	390
Collector Cutoff Current at $-V_{CB} = 50 \text{ V}$	$-I_{CBO}$	-	-	0.5	μA
Emitter Cutoff Current at $-V_{EB} = 4 \text{ V}$	$-I_{EBO}$	-	-	0.5	μA
Collector-Base Breakdown Voltage at $-I_C = 50 \mu\text{A}$	$-V_{CBO}$	80	-	-	V
Emitter-Base Breakdown Voltage at $-I_E = 50 \mu\text{A}$	$-V_{EBO}$	5	-	-	V
Collector-Emitter Breakdown Voltage at $-I_C = 2 \text{ mA}$	$-V_{CEO}$	80	-	-	V
Collector-Emitter Saturation Voltage at $-I_C = 500 \text{ mA}$, $-I_B = 50 \text{ mA}$	$-V_{CE(sat)}$	-	-	0.5	V
Output Capacitance at $-V_{CB} = 10 \text{ V}$, $f = 1 \text{ MHz}$	C_{ob}	-	11	-	pF
Transition Frequency at $-V_{CE} = 10 \text{ V}$, $I_E = 50 \text{ mA}$, $f = 100 \text{ MHz}$	f_T	-	180	-	MHz