


Tape and Reel Specifications and Packaging Specifications for Surface Mount Transistors

Embossed Tape and Reel is used to facilitate automatic pick and place equipment feed requirements. The tape is used as the shipping container for various products and requires a minimum of handling. The antistatic / conductive tape provides a secure cavity for the product when sealed with the "peel-back" cover tape.

- Two Reel Sizes Available (7" and 13")
- SC-59, SC-70 / SOT-323, SOT-23, SOT-523 in 8 mm Tape
- Used for Automatic Pick and Place Feed Systems

Use the standard device title and add the required suffix as listed in the option table on the following page. Note that the individual reels have a finite number of devices depending on the type of product contained in the tape. Also note the minimum lot size is one full reel for each line item, and orders are required to be in increments of the single reel quantity.

SC-59 / SC-70 / SOT-323 / SOT-23 / SOT-523
8 mm



Direction
of feed



EMBOSSED TAPE AND REEL ORDERING INFORMATION

Package	Tape Width (mm)	Pitch		Reel Size		Devices Per Reel and Minimum Order Quantity
		mm	(inch)	mm	(inch)	
SC-70 SOT-323	8 8	4.0 ±0.1	(0.157 ± 0.004)	178 330	(7) (13)	3,000 10,000
SC-59 SOT-23	8 8	4.0 ±0.1	(0.157 ± 0.004)	178 330	(7) (13)	3,000 10,000
SOT-523	8 8	4.0 ±0.1	(0.157 ± 0.004)	178 330	(7) (13)	4,000 15,000